
Python support for the Linux perf profiler

Release 3.13.0a2

Guido van Rossum and the Python development team

January 18, 2024

Python Software Foundation
Email: docs@python.org

Contents

1	How to enable <code>perf</code> profiling support	4
2	How to obtain the best results	4
	Index	5

author

Pablo Galindo

The Linux `perf` profiler is a very powerful tool that allows you to profile and obtain information about the performance of your application. `perf` also has a very vibrant ecosystem of tools that aid with the analysis of the data that it produces.

The main problem with using the `perf` profiler with Python applications is that `perf` only gets information about native symbols, that is, the names of functions and procedures written in C. This means that the names and file names of Python functions in your code will not appear in the output of `perf`.

Since Python 3.12, the interpreter can run in a special mode that allows Python functions to appear in the output of the `perf` profiler. When this mode is enabled, the interpreter will interpose a small piece of code compiled on the fly before the execution of every Python function and it will teach `perf` the relationship between this piece of code and the associated Python function using `perf` map files.

Note: Support for the `perf` profiler is currently only available for Linux on select architectures. Check the output of the `configure` build step or check the output of `python -m sysconfig | grep HAVE_PERF_TRAMPOLINE` to see if your system is supported.

For example, consider the following script:

```
def foo(n):
    result = 0
    for _ in range(n):
        result += 1
    return result
```

(continues on next page)

(continued from previous page)

```
def bar(n):
    foo(n)

def baz(n):
    bar(n)

if __name__ == "__main__":
    baz(1000000)
```

We can run `perf` to sample CPU stack traces at 9999 hertz:

```
$ perf record -F 9999 -g -o perf.data python my_script.py
```

Then we can use `perf report` to analyze the data:

```

$ perf report --stdio -n -g

# Children      Self          Samples  Command      Shared Object      Symbol
# .....      .....      .....      .....      .....      .....
↪ .....
#
    91.08%      0.00%              0  python.exe  python.exe      [...] _start
      |
      |---_start
      |
      |---90.71%--__libc_start_main
          Py_BytesMain
              |
              |---56.88%--pymain_run_python.constprop.0
                  |
                  |---56.13%--_PyRun_AnyFileObject
                      |
                      |---_PyRun_SimpleFileObject
                          |
                          |
                          |---55.02%--run_mod
                              |
                              |---54.65%--PyEval_EvalCode
                                  _PyEval_
↪ EvalFrameDefault
          |
          |
          |---PyObject_
↪ Vectorcall
          |
          |
          |---_PyEval_Vector
              _PyEval_
↪ EvalFrameDefault
          |
          |
          |---PyObject_
↪ Vectorcall
          |
          |
          |---_PyEval_Vector
              _PyEval_
↪ EvalFrameDefault
          |
          |
          |---PyObject_
↪ Vectorcall
          |
          |
          |---_PyEval_Vector
              |
              |---51.67%--_
↪ PyEval_EvalFrameDefault
          |
          |
          |---_
↪ 11.52%--_PyLong_Add
          |
          |
          |
↪ |
          |
          |---2.97%--_PyObject_Malloc

```

(continues on next page)

...

As you can see, the Python functions are not shown in the output, only `_PyEval_EvalFrameDefault` (the function that evaluates the Python bytecode) shows up. Unfortunately that's not very useful because all Python functions use the same C function to evaluate bytecode so we cannot know which Python function corresponds to which bytecode-evaluating function.

Instead, if we run the same experiment with `perf` support enabled we get:

```
$ perf report --stdio -n -g
```

#	Children	Self	Samples	Command	Shared Object	Symbol
#
↪					
#	90.58%	0.36%	1	python.exe	python.exe	[.] _start
	---	_start				
		--89.86%	--	__libc_start_main		
				Py_BytesMain		
			--55.43%	--	pymain_run_python.constprop.0	
				--54.71%	--	_PyRun_AnyFileObject
						_PyRun_SimpleFileObject
					--53.62%	--
						run_mod
					--53.26%	--
						PyEval_EvalCode
						py::<module>:/
↪src/script.py						
						PyEval
↪EvalFrameDefault						
						PyObject_
↪Vectorcall						
						_PyEval_Vector
						py::baz:/src/
↪script.py						
						PyEval
↪EvalFrameDefault						
						PyObject_
↪Vectorcall						
						_PyEval_Vector
						py::bar:/src/
↪script.py						
						PyEval
↪EvalFrameDefault						
						PyObject_
↪Vectorcall						
						_PyEval_Vector
						py::foo:/src/
↪script.py						
						--51.81%
↪PyEval_EvalFrameDefault						--
↪13.77%	--	_PyLong_Add				
↪						

(continues on next page)

1 How to enable `perf` profiling support

perf profiling support can be enabled either from the start using the environment variable `PYTHONPERFSUPPORT` or the `-X perf` option, or dynamically using `sys.activate_stack_trampoline()` and `sys.deactivate_stack_trampoline()`.

The `sys` functions take precedence over the `-X` option, the `-X` option takes precedence over the environment variable.

Example, using the environment variable:

```
$ PYTHONPERFSUPPORT=1 python script.py
$ perf report -g -i perf.data
```

Example, using the `-X` option:

```
$ python -X perf script.py
$ perf report -g -i perf.data
```

Example, using the `sys` APIs in file `example.py`:

```
import sys

sys.activate_stack_trampoline("perf")
do_profiled_stuff()
sys.deactivate_stack_trampoline()

non_profiled_stuff()
```

...then:

```
$ python ./example.py
$ perf report -g -i perf.data
```

2 How to obtain the best results

For best results, Python should be compiled with `CFLAGS="-fno-omit-frame-pointer -mno-omit-leaf-frame-pointer"` as this allows profilers to unwind using only the frame pointer and not on DWARF debug information. This is because as the code that is interposed to allow `perf` support is dynamically generated it doesn't have any DWARF debugging information available.

You can check if your system has been compiled with this flag by running:

```
$ python -m sysconfig | grep 'no-omit-frame-pointer'
```

If you don't see any output it means that your interpreter has not been compiled with frame pointers and therefore it may not be able to show Python functions in the output of `perf`.

Index

E

environment variable
 PYTHONPERFSUPPORT, 4

P

PYTHONPERFSUPPORT, 4